

COLUMN DRILL MACHINE FOLLOW B40E

Ref: B40E FOLLOW



Tech specs

Brand	FOLLOW
Drilling capacity in steel 60kg	40
Drilling capacity cast iron 200HB	50
Capacity steel thread 60Kg	M-24
Tapping capacity in cast-iron 200 HB	M-40
Transmission	Engranés
Automatic feed	Si
Clutch	Electromagnético
Feed number and range	4 (0,1 - 0,2 - 0,3 - 0,4)
Speed number and range	(12) 52-1400
Power of the main motor	2,2
Tapper	MT4
Spindle travel	200
Distance spindle center/ column	360
Column diameter	160
Table surface	580x460
Base surface	445x435
Max. distance between the spindle and the table	590
Distance max. between spindle to base	1175
Base T slot size	2-T14
Electrical voltage	220-380 V - 50/60 Hz
Dimensions (length x width x height)	940x680x2402
Net/ brut weigth	655/710



Standard equipment

- Digital display R.P.M.
- Depth readout display
- Powered table
- Tilting and swivel table
- Depth setting
- Drill ejector
- Coolant system
- Tapping system with turning inversion
- 3 MT sleeve
- Drill chuck capacity 1-13mm
- Sensitive Wheel
- Work Light
- Tool box
- CE certificate

Images

