

---

## COLUMN DRILL MACHINE FOLLOW B32IE

---

Ref: B32IE FOLLOW



## Tech specs

<b>Brand</b>	FOLLOW
<b>Drilling capacity in steel 60kg</b>	32
<b>Drilling capacity cast iron 200HB</b>	42
<b>Capacity steel thread 60Kg</b>	M-22
<b>Tapping capacity in cast-iron 200 HB</b>	M-32
<b>Transmission</b>	Engranés
<b>Automatic feed</b>	Si
<b>Clutch</b>	Electromagnético
<b>Feed number and range</b>	3(0,1-0,2-0,3)
<b>Speed number and range</b>	(12) 125-3030
<b>Power of the main motor</b>	1/1,2
<b>Tapper</b>	MT4
<b>Spindle travel</b>	155
<b>Distance spindle center/ column</b>	320
<b>Column diameter</b>	120
<b>Table surface</b>	500x420
<b>Base surface</b>	370x363
<b>Max. distance between the spindle and the table</b>	620
<b>Distance max. between spindle to base</b>	1265
<b>Base T slot size</b>	2-T14
<b>Electrical voltage</b>	220-380 V - 50/60 Hz
<b>Dimensions (length x width x height)</b>	850x500x2220
<b>Net/ brut weigth</b>	510/560



## Standard equipment

---

- Digital display R.P.M.
- Depth readout display
- Powered table
- Tilting and swivel table
- Depth setting
- Drill ejector
- Coolant system
- Tapping system with turning inversion
- 3 MT sleeve
- Drill chuck capacity 1-13mm
- Sensitive Wheel
- Work Light
- Tool box
- CE certificate

## Images

---

