

COLUMN DRILL MACHINE FOLLOW B30A

Ref: B30A FOLLOW



Tech specs

Brand	FOLLOW
Drilling capacity in steel 60kg	35
Drilling capacity cast iron 200HB	35
Capacity steel thread 60Kg	M-20
Tapping capacity in cast-iron 200 HB	M-30
Transmission	Engranes
Automatic feed	Si
Clutch	Mecánico
Feed number and range	3(0,1-0,2-0,3)
Speed number and range	(12) 125-3030
Power of the main motor	1/1,2
Tapper	MT4
Spindle travel	155
Distance spindle center/ column	320
Column diameter	120
Table surface	500x420
Base surface	370x360
Max. distance between the spindle and the table	625
Distance max. between spindle to base	1180
Base T slot size	2-T14
Electrical voltage	220-380 V - 50/60 Hz
Dimensions (length x width x height)	815x510x2140
Net/ brut weigth	430/475



Standard equipment

- Digital display R.P.M.
- Depth readout display
- Powered table
- Tilting and swivel table
- Depth setting
- Drill ejector
- Coolant system
- Tapping system with turning inversion
- 3 MT sleeve
- Drill chuck capacity 1-13mm
- Sensitive Wheel
- Work Light
- Tool box
- CE certificate

Images

