

---

## COLUMN DRILL MACHINE FOLLOW M30R

---

Ref: M30R FOLLOW



## Tech specs

<b>Brand</b>	FOLLOW
<b>Drilling capacity in steel 60kg</b>	35
<b>Drilling capacity cast iron 200HB</b>	40
<b>Capacity steel thread 60Kg</b>	M-20
<b>Tapping capacity in cast-iron 200 HB</b>	M-30
<b>Transmission</b>	Engranés
<b>Automatic feed</b>	No (manual)
<b>Speed number and range</b>	(12)125-3030
<b>Power of the main motor</b>	1/1,2
<b>Tapper</b>	MT4
<b>Spindle travel</b>	160
<b>Distance spindle center/ column</b>	320
<b>Column diameter</b>	120
<b>Table surface</b>	500x420
<b>Base surface</b>	370x360
<b>Max. distance between the spindle and the table</b>	625
<b>Distance max. between spindle to base</b>	1180
<b>Base T slot size</b>	2-T14
<b>Electrical voltage</b>	220-380 V - 50/60 Hz
<b>Dimensions (length x width x height)</b>	835x510x1730
<b>Net/ brut weigth</b>	430/475



## Standard equipment

---

- Tilting and swivelling of the table
- Depth adjustment
- Drill ejector
- Cooling system
- 3 MT reduction sleeve
- Drill chuck capacity 1-13mm
- Work light
- CE Certified



## Images

---

