

---

## COLUMN DRILL MACHINE FOLLOW M25R

---

Ref: M25R FOLLOW



## Tech specs

<b>Brand</b>	FOLLOW
<b>Drilling capacity in steel 60kg</b>	25
<b>Drilling capacity cast iron 200HB</b>	35
<b>Capacity steel thread 60Kg</b>	M-18
<b>Tapping capacity in cast-iron 200 HB</b>	M-25
<b>Transmission</b>	Engranés
<b>Automatic feed</b>	No (manual)
<b>Speed number and range</b>	(6) 125-2825
<b>Power of the main motor</b>	0,75
<b>Tapper</b>	MT3
<b>Spindle travel</b>	110
<b>Distance spindle center/ column</b>	240
<b>Column diameter</b>	100
<b>Table surface</b>	400x330
<b>Base surface</b>	310x340
<b>Max. distance between the spindle and the table</b>	675
<b>Distance max. between spindle to base</b>	1100
<b>Base T slot size</b>	2-T14
<b>Electrical voltage</b>	220-380 V - 50/60 Hz
<b>Dimensions (length x width x height)</b>	700x460x1925
<b>Net/ brut weigth</b>	410/455



## Standard equipment

---

Tilting and swivell table  
Depth setting  
Drill ejector  
Cooling system  
3 MT reducer sleeve  
Drill chuck capacity 1-13mm  
Work light  
CE Certified



## Images

---

