

---

## DRILLING MILLING MACHINE FOLLOW TF50

---

Ref: TF50 FOLLOW



## Tech specs

<b>Brand</b>	FOLLOW
<b>Max. boring capacity</b>	50
<b>Max. reaming capacity</b>	50
<b>Max milling capacity</b>	25
<b>Spindle travel (drill depth)</b>	130
<b>Headstock rotation</b>	± 45°
<b>Transmission</b>	Engranes
<b>Longitudinal and cross feed</b>	AUTOMAT.
<b>Table travel</b>	380x200
<b>Dimensions of the table</b>	800x240
<b>Tapper</b>	MT4
<b>Feed number and range</b>	8 (115-1750)
<b>Max. distance between the spindle and the table</b>	0-400
<b>Distance spindle center/ column</b>	320
<b>Column type</b>	Prismatic
<b>Main motor power</b>	0.85/1.5
<b>Dimensions (length x width x height)</b>	1200x1200x1700
<b>Net/ brut weigth</b>	500

## Standard equipment

---

- FAGOR digital readout X,Y,Z
- Sensitive Wheel
- 2 pcs increasers from MT4 to MT3 & MT2
- Drill chuck capacity 3-16mm
- Tool holder MT4
- Mechanic vice 160mm with swivel base
- Work light
- Tool box
- CE certificate



## Images

---

