

AUTOMATIC SURFACE GRINDER FOLLOW RSA510

Ref: RSA510 FOLLOW



Tech specs

Brand	FOLLOW
Surface worktable	510x250
Max. rectification area	510x250
Max. work table longitudinal travel	575
Max. cross travel of the table	280
Max. distance between the spindle center/ table	535
Max. load of magnetic chuck	300
Velocidad husillo (rpm)	2850
Table speed	5-25
Automatic transversal movement of the bench	0,5-12
Vertical handwheel precision	0,001
Vertical handwheel 1 turn	2
Precision transversal handwheel	0,02
Cross handwheel 1 turn	5
Power of headstock motor	2,2
Power of hydraulic motor	1,5
Power of cross feed motor	0,06
Power of cooling motor	0,09
Electrical voltage	220-380 V - 50/60 Hz
Electromagnetic chuck dimensions	500x250
Grinding wheel [øExt. x width x ø In.]	200x25x32
Dimensions (length x width x height)	1650x2000x2140
Weight	1680/1930



Standard equipment



- Electromagnetic Chuck
(magnetizer/demagnetizer)

- Coolant System

- Diamond Support
- Automatic Movements X -Y - Z

- FAGOR Y Z digital readout

- Y axis ballscrew

- Magnetic chip separator

- Overhead parallel dresser

- Work light

- CE certificate