

---

## UNIVERSAL MILLING MACHINE FOLLOW FU1250

---

Ref: FU1250 FOLLOW



## Tech specs

<b>Brand</b>	FOLLOW
<b>Worktable surface</b>	1250 x 320
<b>T-slot</b>	3x16
<b>Max. weight over table</b>	200
<b>Longitudinal travel</b>	1000
<b>Cross slide travel</b>	280
<b>Longitudinal feed</b>	(8) 30 - 740
<b>Cross feed</b>	(8) 30-740
<b>Vertical feed</b>	motorizado
<b>Longitudinal and cross rapid movement</b>	1300
<b>Rapid vertical movement</b>	600
<b>Taper of ram headstock</b>	ISO40
<b>Boring taper</b>	ISO40
<b>Ram headstock speed range</b>	35-1600
<b>Number of ram headstock speeds</b>	11
<b>Range of speeds</b>	40-1300
<b>Ram power</b>	3
<b>Power ram headstock</b>	3
<b>Ram movement</b>	MANUAL
<b>Ram travel</b>	600
<b>Table feed</b>	Automatico
<b>Distance between the front spindle and the ram slide</b>	240
<b>Distance headstock/ table</b>	250-660
<b>Dimensions (length x width x height)</b>	2300x2200x2115
<b>Net weight</b>	2000



## Standard equipment

---

- FAGOR digital X, Y, Z
- Automatic movement X,Y.
- Motorized Z axis
- Universal headstock ISO 40.
- Mill holder shaft  $\varnothing$  32\*500
- Mill holder shaft  $\varnothing$  27\*500
- Clip holder set ISO 40
- 2 Centre rest
- Mechanical vice 160 mm. With swivel base
- Coolant collect tray.
- Coolant system.
- Work light.
- Tool box.
- CE certificate

## Images

---

