

## PARALLEL LATHE FOLLOW CE460VX1000

Ref: CE460vX1000 FOLLOW



## Tech specs

|                                             |                |
|---------------------------------------------|----------------|
| <b>Brand</b>                                | FOLLOW         |
| <b>Height of points</b>                     | 230 mm         |
| <b>Distance between centers</b>             | 1000           |
| <b>Swing over bed</b>                       | 460            |
| <b>Swing over ram</b>                       | 700            |
| <b>Swing over carriage</b>                  | 300            |
| <b>Bed width</b>                            | 340            |
| <b>Length gap</b>                           | 310            |
| <b>width charriot</b>                       | 130            |
| <b>Main spindle hole</b>                    | 80             |
| <b>Number of speed ranges of spindle</b>    | 25-1800 r.p.m  |
| <b>Spindle nose</b>                         | CAMLOCK Nº8    |
| <b>Main spindle morse taper</b>             | 7 CM/MT        |
| <b>Longitudinal feed</b>                    | 0,041-2,46     |
| <b>Cross feed</b>                           | 0,02-1,25      |
| <b>Metric pitch</b>                         | (24) 0,5-20    |
| <b>Pasos Whitworth</b>                      | (61)1,5/8-72   |
| <b>Modular pitch</b>                        | (20) 0,25-10   |
| <b>Diametral pitch</b>                      | (45) 96-31/4   |
| <b>Master spindle pitch</b>                 | Ø/ 40 x 12DP   |
| <b>Cross carriage travel</b>                | 290            |
| <b>Carriage travel</b>                      | 135            |
| <b>Max. dimension of tool</b>               | 25x25          |
| <b>Tailstock morse taper</b>                | 5 CM/MT        |
| <b>Power of the main motor</b>              | 5,5/7,5        |
| <b>Power of motor pump</b>                  | 0,09/0,12      |
| <b>Electrical voltage</b>                   | 230-400/50 Hz  |
| <b>Dimensions (length x width x height)</b> | 2480x1150x1600 |
| <b>Net weight</b>                           | 2700           |
| <b>Quill diameter</b>                       | 75             |
| <b>Quill travel</b>                         | 150            |



## Standard equipment

---

- 3 jaw universal chuck Ø250mm
- 4 independent jaw chuck Ø320mm
- Faceplate Ø 410mm
- Drive plate Ø275mm
- Display FAGOR X,Y
- Live center
- 2 dead centers CM3
- Emergency brake
- Steady rest
- Follow rest
- Quick change tool post with 4 tool holder
- Coolant system
- Work light
- Tool box
- Certificate CE

## Images

---

